

BD-6530BT

Wireless Area Imaging Scanner

Durable
Reliable
Economical
Ergonomic design




Economical High Performance Wireless 2D Scanner

The BD-6530BT is 2D wireless scanner which is able to communicate to the devices such as laptops, tablet and mobile phone devices. It has connected up to 90M work range. It combines energy efficiency and high performance with the unprecedented versatility.

The BD-6530BT has a secure range of up to 90 meters and an aggressive scan performance on most of 1D barcodes and 2D barcodes. The BD-6530BT's high performance, ergonomic design combines simple reliability with the flexibility and convenience of a wireless scanner. It's perfect for using in retail, document/billing process and banking /finance environment, health care, medical industry and warehousing solution.





Typical Performance 性能

Narrow Width	Depth of Field 景深 (掃描距離)
5 mil	25 mm – 70 mm
6.7 mil	30 mm – 35 mm
13 mil	55 mm – 170 mm
20 mil	15 mm – 190 mm
40 mil	80 mm – 350 mm

Resolution 解析度 : 4 mil

Performance may be impacted by bar code quality and environmental conditions (性能可能會受到條碼品質與使用環境不同而影響)

General 一般特性

Interface 連接介面	HID-USB / USB-COM
Barcodes Supported (1D) 可讀取的1維條碼種類	All UPC/EAN/JAN, Code 39, Code 39 full ASCII, Code 32 /Italian Pharmacode, Code 128, CODABAR, Interleaved 2 of 5, MSI, Code 93, GS1 DataBAR 14, GS1 DataBar Expanded, GS1 Expanded Stacked, GS1 Data Bar Limited, GS1 Composite Component A/B/C
Barcodes Supported (2D) 可讀取的2維條碼種類	PDF417, Micro PDF417, DataMatrix, QR Code, Micro QR Code, Aztec, Maxicode
Communication 通訊	
RF Standard 無線傳輸規格	藍牙 4.0 版本
Working Distance 傳輸距離	90公尺 (在開放空間)
Optical 光學	
Optical Sensor 感測元件	648(H) x 488 (V) pixels
Light Source 光源	紅光 LED (610nm) / 白光 LED 6000 – 6500K
Resolution 解析度	4 mil (Code 39), 6.7 mil (DataMatrix)
Depth of Field 景深	55 – 170 mm (13Mil)
Scan Rate 掃描速率	60次掃描/秒
PCS 最低印刷對比度	→30% @ UPC/EAN 100%
Indicator 掃描提示	LED、蜂鳴聲
Electrical 電力	
Voltage 電壓	DC 3.3V ± 5%
Scanning Currents 掃描電流	< 350 mA
Standby Currents 待機電流	<100 mA
Environment 操作環境	
Operating Temperature 操作溫度	0°C to 40°C (32°F to 104°F)
Storage Temperature 儲存溫度	-40°C to 70°C (-40°F to 158°F)
Operating Humidity 操作溼度	10% - 95% RH (非冷凝)
Storage Humidity 儲存溼度	10% - 85% RH (非冷凝)
Drop 耐摔高度	1.5公尺
Light Levels 照明度	100,000 lux
Physical 物理特性	
Weight 重量	190g (不含底座)
Dimensions 尺寸	82.53mm (長) x 66.4mm (寬) x 162.08mm (高)
Housing Material 外殼材質	ABS 塑膠
Warranty 保固	1 年
Certificate 安規認證	BSMI / CE / FCC / NCC
Battery 電池	
Battery Type 電池種類	鋰離子電池 3.7V
Battery Capacity 電池容量	2600mAh, 每充電掃描 約7萬次 (連續讀取)
Charge 充電方式	USB充電線或底座
Time of Charge 充電時間	大約5小時 (USB充電線)